

View Online at <https://aerobasegroup.com/nsn/4720-00-482-8191>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.312 inches

Temperature Rating:

-55.00 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.680 inches

Minimum Inside Bending Radius:

1.250 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and 1st layer braided polyester cord and outer layer braided textile yarn

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.500 inches

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0