

View Online at <https://aerobasegroup.com/nsn/4720-00-483-0701>

Cross Sectional Shape:

Round

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.270 inches 1st end

Outside Diameter:

1.219 inches

Minimum Inside Bending Radius:

9.500 inches

Flange Outside Diameter:

1.500 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2250.0 pounds per square inch

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Cold resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.250 inches

Flange Style:

Round w/ out bolt holes 1st end

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0