NSN 4720-00-483-2588



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-483-2588 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.875 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.500 inches **Minimum Inside Bending Radius:** 9.620 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and 3rd layer braided fabric and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch **Inside Surface Condition:** Smooth **Thread Series Designator:** Unjf 1st end

Demilitarization: No

Unit Of Measure:

Shelf Life:

N/a

NSN 4720-00-483-2588

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0