Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-0562

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.300 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit an	d 275.0 degrees fahrenheit single response
Outside Diameter:	
0.656 inches	
Minimum Inside Bending R	adius:
5.000 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st e	nd
Burst Test Pressure:	
14000.0 pounds per square i	inch
Layer Composition And Lo	ocation:
2nd layer spirally wrapped po	olytetrafluoroethylene fabric and 1st layer spirally wrapped corrosion resistant steel fabric and outer layer
praided corrosion resistant s	teel wire
Maximum Operating Press	ure:
3000.0 pounds per square in	ich
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square in	ich
Outer Covering Environme	Intal Protection:
Corrosion resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Le	ngth:
18.000 inches working	-
-	
_	
Thread Series Designator: Unjf 1st end	

## NSN 4720-00-484-0562

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

