## NSN 4720-00-484-2411

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-2411

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.312 inches   |
| Tempurature Rating:  |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:  |
| 0.437 inches   |
| Minimum Inside Bending Radius:   |
| 2.500 inches   |
| Connection Style:  |
| Swivel nut flare 2nd end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 8800.0 pounds per square inch  |
| Layer Composition And Location:  |
| Outer layer braided steel wire   |
| Maximum Operating Pressure:  |
| 1500.0 pounds per square inch  |
| Thread Size:   |
| 0.500 inches 2nd end   |
| Seat Angle:  |
| 45.0 degrees 2nd end   |
| Flow Angle:  |
| 90.0 degrees 2nd end   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 52.000 inches  |
| Thread Series Designator:  |
| Unf 2nd end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

-

## NSN 4720-00-484-2411

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0