Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-3531

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

# Inside Diameter:

0.313 inches

#### **Tempurature Rating:**

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.446 inches

Minimum Inside Bending Radius:

4.000 inches

#### **Exterior Color:**

Natural

### **Connection Style:**

Swivel nut, flareless 1st end

### End Connection Design:

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

# **Features Provided:**

Electrostatic discharge capability

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.562 inches 1st end

### Seat Angle:

12.0 degrees 1st end

### Hydrostatic Test Pressure:

3000.0 pounds per square inch

# **Outer Covering Environmental Protection:**

Corrosion resistant

Vacuum In Torr:

50.8

### Inside Surface Condition:

Smooth



Measuring Method And Length:

49.000 inches working

**Thread Series Designator:** 

Unjf 1st end

Specification Data:

96906-ms8001 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0