## NSN 4720-00-484-8305

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-8305

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.480 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and 6th layer braided fiber and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
30.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
43.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Uns 1st end

## NSN 4720-00-484-8305

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0