NSN 4720-00-484-8308

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-8308

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.484 inches
Minimum Inside Bending Radius:
4.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided textile yarn and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
30.0 degrees 2nd end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Cold resistant and mildew resistant and oil resistant
Inside Surface Condition:

NSN 4720-00-484-8308

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
18.250 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and water single response
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0