Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-484-9017

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.406 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees fahr	enheit single response
Outside Diameter:	
0.562 inches	
Minimum Inside Bending Radius:	
4.600 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Vacuum In Torr:	
50.8	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
48.000 inches working	

NSN 4720-00-484-9017

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 1st end

Specification Data:

19315-2132642-10 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0