NSN 4720-00-485-7826

Cross Sectional Shape:

Round

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-485-7826

Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.438 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
0.610 inches			
Minimum Inside Bending Radius:			
5.250 inches			
Exterior Color:			
Natural			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Nuts drilled for lockwire			
Thready Qty Per Inch (tpi):			
18 1st end			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.750 inches 1st end			
Seat Angle:			
12.0 degrees 1st end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Corrosion resistant			
Inside Surface Condition:			

NSN 4720-00-485-7826

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:
-----------	--------	-----	---------

12.500 inches

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0