Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-485-7866

View Online at https://aerobasegroup.com/nsn/4720-00-485-7866
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single respons
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Natural
End Application:
Grumman a-10 aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
2200.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1100.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth



Measuring Method And Length:

120.000 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms2458 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-26626 spec.