Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-488-3537

| <b>Cross Sectional</b> | Shape: |
|------------------------|--------|
| Round                  |        |

Thread Class:

2b 1st end

### **Thread Direction:**

Right-hand 1st end

# **Inside Diameter:**

0.750 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

1.170 inches

Minimum Inside Bending Radius:

9.500 inches

#### **Exterior Color:**

Natural

### **Connection Style:**

Swivel nut flare 2nd end

### End Connection Design:

Straight 1st end

# **Connection Type:**

Threaded internal tube 1st end

# Thready Qty Per Inch (tpi):

12 2nd end

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer molded rubber, synthetic and outer layer molded rubber, synthetic

#### Maximum Operating Pressure:

2250.0 pounds per square inch

#### **Thread Size:**

1.062 inches 2nd end

#### Seat Angle:

37.0 degrees 2nd end

#### Flow Angle:

90.0 degrees 2nd end

# **Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

# Inside Surface Condition:

Smooth

#### Measuring Method And Length:

48.000 inches

Nonmetallic Hose Assembly - Page 2 of 2



Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

