## NSN 4720-00-489-3638

**Cross Sectional Shape:** 

Unjf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-489-3638

| Round   |
|---|
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.625 inches  |
| Minimum Inside Bending Radius:  |
| 4.000 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 1000.0 pounds per square inch   |
| Maximum Operating Pressure:   |
| 150.0 pounds per square inch  |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 300.0 pounds per square inch  |
| Outer Covering Environmental Protection:  |
| Abrasion resistant and fuel resistant and oil resistant                               |
| Vacuum In Torr:   |
| 254.0   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 99.000 inches working   |
| Media For Which Designed:   |
| Air single response   |
| Thread Series Designator:   |

## NSN 4720-00-489-3638

Nonmetallic Hose Assembly - Page 2 of 2



| Specification Data | Spe | ecifica | ition | Data: |
|--------------------|-----|---------|-------|-------|
|--------------------|-----|---------|-------|-------|

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0