# NSN 4720-00-489-5722



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-489-5722 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.485 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 24 2nd end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided rayon cord

### **Maximum Operating Pressure:**

250.0 pounds per square inch

#### **Thread Size:**

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

# **Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and oil resistant

# **Inside Surface Condition:**

Smooth

# **Measuring Method And Length:**

15.000 inches

# NSN 4720-00-489-5722

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ned:

Air and fuel/oil, hydrocarbon and water single response

**Thread Series Designator:** 

Uns 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0