Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-489-5755

Cross Sectional Shane	
Cross Sectional Shape: Round	
Thread Class:	
2b 1st end Thread Direction:	
Right-hand 1st end Inside Diameter:	
0.620 inches	
Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.910 inches	
Minimum Inside Bending Radius:	
6.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided textile yarn and 1st layer braided textile yarn	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
38.125 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0