## NSN 4720-00-489-8235

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-489-8235 **Cross Sectional Shape:** Round **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.423 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 0.750 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 2nd end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer spirally wrapped corrosion resistant steel fabric **Maximum Operating Pressure:** 6250.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 8300.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end

**Outer Covering Environmental Protection:** Corrosion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

6.250 inches working

## NSN 4720-00-489-8235

Nonmetallic Hose Assembly - Page 2 of 2



Sı	oec	ial	Fe	atı	ur	es	:
----	-----	-----	----	-----	----	----	---

Permanently attached fittings

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0