Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-490-6348

Cross Section	onal Shape:
Round	
Thread Clas	S:
2b 1st end	
Thread Dire	ction:
Right-hand 1	st end
Inside Diam	eter:
0.188 inches	
Tempurature	e Rating:
-40.0 degree	s fahrenheit and 275.0 degrees fahrenheit single response
Outside Dia	meter:
0.516 inches	
Minimum Ins	side Bending Radius:
3.000 inches	
Connection	Style:
Swivel nut fla	ire 1st end
End Connec	tion Design:
Straight 1st e	and
Connection	Туре:
Threaded inte	ernal tube 1st end
Burst Test P	Pressure:
12000.0 pour	nds per square inch
Layer Comp	osition And Location:
2nd layer bra	ided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord
Maximum O	perating Pressure:
3000.0 pound	ds per square inch
Thread Size	
0.438 inches	1st end
Seat Angle:	
37.0 degrees	1st end
Vacuum In T	orr:
50.8	
Inside Surfa	ce Condition:
Smooth	
Measuring M	lethod And Length:
64.500 inche	s working
Media For W	/hich Designed:
Air and fuel/	oil, hydrocarbon single response
Thread Serie	es Designator:
Unf 1st end	
Shelf Life:	
N/a	

NSN 4720-00-490-6348

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0