NSN 4720-00-491-6534

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-491-6534

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.593 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.437 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches working
Media For Which Designed:
Air single response

Unf 2nd end

Thread Series Designator:

NSN 4720-00-491-6534

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0