NSN 4720-00-492-3580

Cross Sectional Shape:

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

Round

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-492-3580

Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.490 inches
Minimum Inside Bending Radius:
4.000 inches
Inner Conveying Tube Style:
Helical close-pitch corrugated
Exterior Color:
Natural
Connection Style:
Swivel nut, gas 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal gas cylinder 1st end
Features Provided:
Identical ends
Burst Test Pressure:
14000.0 pounds per square inch
14000.0 pounds per square inch Layer Composition And Location:
Layer Composition And Location:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 48.000 inches
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.908 inches 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 48.000 inches Seat Radius:

NSN 4720-00-492-3580

Metallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-dtl-26499 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0