

View Online at <https://aerobasegroup.com/nsn/4720-00-492-3580>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.490 inches

Minimum Inside Bending Radius:

4.000 inches

Inner Conveying Tube Style:

Helical close-pitch corrugated

Exterior Color:

Natural

Connection Style:

Swivel nut, gas 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal gas cylinder 1st end

Features Provided:

Identical ends

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.908 inches 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

48.000 inches

Seat Radius:

0.203 inches 1st end

Thread Series Designator:

Ngo 1st end

Specification Data:

81349-mil-dtl-26499 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0