Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-492-4851

Cross Sectional S	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rati	na.
	enheit and 275.0 degrees fahrenheit single response
Outside Diameter	
0.516 inches	
Minimum Inside E	anding Padius
3.000 inches	
Connection Style	
Swivel nut flare 1st	
End Connection I	
Straight 1st end	
Connection Type:	
Threaded internal	
Thready Qty Per I	
20 1st end	
Burst Test Pressu	Ire-
12000.0 pounds pe	
Layer Compositio	
	teel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord
Maximum Operati	
3000.0 pounds per	-
Thread Size:	
0.438 inches 1st e	nd
Seat Angle:	
37.0 degrees 1st e	nd
Vacuum In Torr:	
50.8	
Inside Surface Co	ndition:
Smooth	
Measuring Metho	d And Length:
72.500 inches wor	
Media For Which	-
	drocarbon single response
Thread Series De	
Unf 1st end	-

NSN 4720-00-492-4851

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

