

View Online at <https://aerobasegroup.com/nsn/4720-00-492-6756>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.312 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Minimum Inside Bending Radius:**

4.500 inches

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

20 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

25000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally laid corrosion resistant steel wire

**Maximum Operating Pressure:**

6250.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

125000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and hydraulic solution resistant and oil resistant and weatherproof

**Vacuum In Torr:**

0.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.000 inches

**Special Features:**

Inner conveying tube material-rubber, chloroprene

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0