

View Online at <https://aerobasegroup.com/nsn/4720-00-494-0756>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.852 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.390 inches

Minimum Inside Bending Radius:

9.625 inches

Angle Between Rigid Elbow Fittings In Deg:

0.0

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Elbow 2nd end

End Fitting Component And Material:

Complete fitting steel 1st end

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.375 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 50599, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0