NSN 4720-00-494-1740

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-494-1740

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
2.310 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated braided fabric and 1st layer braided corrosion resistant steel wire, partial coverage
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Npt 1st end

NSN 4720-00-494-1740

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0