

View Online at <https://aerobasegroup.com/nsn/4720-00-494-8195>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

2.310 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

57.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0