Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-495-1266

Cross Sectional S	shape:
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rati	ng:
-	enheit and 200.0 degrees fahrenheit single response
Outside Diameter	
0.750 inches	
Minimum Inside B	ending Radius:
1.750 inches	
Connection Style:	
Swivel, plain 2nd e	
End Connection	
Straight 2nd end	-
Connection Type:	
Threaded external	
Burst Test Pressu	ire:
900.0 pounds per s	square inch
Layer Compositio	n And Location:
2nd layer braided t	extile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operati	ng Pressure:
225.0 pounds per s	equare inch
Thread Size:	
0.250 inches 2nd e	nd
Seat Angle:	
30.0 degrees 1st e	nd
Inside Surface Co	ndition:
Smooth	
Measuring Metho	d And Length:
29.000 inches	
Media For Which	Designed:
Air single response	
Thread Series Des	signator:
Nptf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-00-495-1266

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

