NSN 4720-00-495-4420

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-495-4420 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.516 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 65.500 inches working Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:**

N/a

Unf 1st end Shelf Life:

NSN 4720-00-495-4420

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0