

View Online at <https://aerobasegroup.com/nsn/4720-00-496-9527>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.069 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Natural

Hose Or Tubing Specification/std Data:

Sae 100r2a standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

20000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided steel wire

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.000 inches working

Special Features:

Inner conveying tube material-rubber, synthetic

Thread Series Designator:

Unf 1st end

Specification Data:

Sae 100r2a national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0