

View Online at <https://aerobasegroup.com/nsn/4720-00-504-1452>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

1.850 inches

**Minimum Inside Bending Radius:**

16.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

26.0

**Flange Outside Diameter:**

2.000 inches 1st end

**Connection Style:**

Plain swivel w/ gasket groove 1st end

**End Flange Construction:**

Split 1st end

**End Connection Design:**

Elbow 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Plain face flange 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally laid steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.750 inches working

**Flange Style:**

Round w/ out bolt holes 1st end

**Special Features:**

Inner conveying tube material-rubber, synthetic; two 90 degrees bends on one end, 12.680 in. C to c

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0