NSN 4720-00-504-2932

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-504-2932

Cross Sectional Shape:						
Round						
Thread Class:						
3b 2nd end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.313 inches						
Tempurature Rating:						
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response						
Outside Diameter:						
0.562 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 2nd end						
Features Provided:						
Electrostatic discharge capability						
Thready Qty Per Inch (tpi):						
18 1st end						
Burst Test Pressure:						
14000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
3000.0 pounds per square inch						
Thread Size:						
0.562 inches 1st end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
6000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Corrosion resistant						
Inside Surface Condition:						

Special Features:

With polytetrafluoroethylene chafe guard

NSN 4720-00-504-2932

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0