Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-506-9459

-	
	ess Sectional Shape:
Rou	
	ead Direction:
-	ht-hand 1st end
	ide Diameter:
	ween 0.367 inches and 0.398 inches
	npurature Rating:
-40	.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Out	tside Diameter:
Bet	ween 0.750 inches and 0.812 inches
Min	imum Inside Bending Radius:
5.0	00 inches
Со	nnection Style:
Inve	erted flare 1st end
End	d Connection Design:
Stra	aight 1st end
Со	nnection Type:
Thr	eaded external pipe 1st end
Bui	rst Test Pressure:
900	0.0 pounds per square inch
Lay	ver Composition And Location:
Out	er layer rubber impregnated braided fabric and 1st layer braided wire
Ma	ximum Operating Pressure:
225	0.0 pounds per square inch
Thr	ead Size:
0.3	75 inches 1st end
Sea	at Angle:
30.0	0 degrees 1st end
Нус	drostatic Test Pressure:
450	0.0 pounds per square inch
Out	ter Covering Environmental Protection:
Oil	resistant and weatherproof
Ins	ide Surface Condition:
Sm	ooth
Me	asuring Method And Length:
42.0	000 inches
Me	dia For Which Designed:
Fue	el/oil, hydrocarbon single response
Thr	ead Series Designator:
	1st end
Sho	elf Life:
N/a	

NSN 4720-00-506-9459

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0