Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-506-9493

Crass Sectional Shane
Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.812 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
38.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

NSN 4720-00-506-9493

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

