## NSN 4720-00-507-0236

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-507-0236

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.880 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.230 inches
Minimum Inside Bending Radius:
7.380 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and 1st layer braided textile yarn and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Vacuum In Torr:

254.0

## NSN 4720-00-507-0236

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
15.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0