NSN 4720-00-507-4269

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-507-4269

Cross Sectional Shape:						
Round						
Thread Class:						
2b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.391 inches						
Tempurature Rating:						
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response						
Outside Diameter:						
0.765 inches						
Minimum Inside Bending Radius:						
5.750 inches						
Connection Style:						
Swivel nut, flareless 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Electrostatic discharge capability						
Burst Test Pressure:						
14000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
3000.0 pounds per square inch						
Thread Size:						
0.750 inches 1st end						
Seat Angle:						
12.0 degrees 1st end						
Hydrostatic Test Pressure:						
6000.0 pounds per square inch						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
16.250 inches working						
Thread Series Designator:						
Unf 1st end						
Shelf Life:						

NSN 4720-00-507-4269

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0