

View Online at <https://aerobasegroup.com/nsn/4720-00-508-1558>

Cross Sectional Shape:

Round

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Flange Thickness:

0.104 inches 2nd end

Outside Diameter:

2.219 inches

Minimum Inside Bending Radius:

13.250 inches

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 2nd end

Flange Width:

3.000 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.344 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Plain face flange 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

1400.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.000 inches

Second End Swivel Action Capability:

Included

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Inner conveying tube material-rubber

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0