

View Online at <https://aerobasegroup.com/nsn/4720-00-512-4359>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.183 inches and 0.204 inches

Outside Diameter:

Between 0.500 inches and 0.539 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Outer Covering Environmental Protection:

Fire resistant and fuel resistant and mildew resistant and oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.375 inches excluding end fittings and 17.625 inches excluding end fittings

Special Markings:

With gasoline, oil and water resistant yellow markings every 9 inches or less along entire length of hose

Thread Series Designator:

Unf 1st end

Fsc Application Data:

Hose assemblies, nonmetallic, except fire fighting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0