

View Online at <https://aerobasegroup.com/nsn/4720-00-513-7890>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

2.500 inches

Outside Diameter:

3.125 inches

Minimum Inside Bending Radius:

15.000 inches

Hose Or Tubing Specification/std Data:

Zz-h-561 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded internal hose 1st end

Thready Qty Per Inch (tpi):

7-1/2 2nd end

Second End Relationship With First End:

Not identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer helix copper coil

Thread Size:

2.500 inches 2nd end

Hydrostatic Test Pressure:

100.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Water, salt single response

Thread Series Designator:

Nh 2nd end

Specification Data:

Zz-h-561 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0