

View Online at <https://aerobasegroup.com/nsn/4720-00-515-0314>

Cross Sectional Shape:

Round

Inside Diameter:

0.937 inches

Temperature Rating:

-65.0 degrees fahrenheit and 350.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 2nd end

Outside Diameter:

1.312 inches

Minimum Inside Bending Radius:

5.000 inches

Angle Between Rigid Elbow Fittings In Deg:

233.0

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.188 inches 1st end

Flange Width:

2.188 inches 1st end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.266 inches and 0.276 inches 2nd end

Raised Face Height:

0.015 inches 2nd end

Raised Face Diameter:

1.854 inches 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

300.0 pounds per square inch

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Convuluted

Measuring Method And Length:

37.750 inches working and 38.250 inches working

Flange Style:

Rectangular (includes square) 2nd end

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 1p322, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0