

View Online at <https://aerobasegroup.com/nsn/4720-00-515-0314>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.937 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 350.0 degrees fahrenheit single response

**Flange Thickness:**

0.297 inches 2nd end

**Outside Diameter:**

1.312 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

233.0

**Center To Center Distance Between Bolt Holes Along Width:**

1.656 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.656 inches 1st end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.188 inches 1st end

**Flange Width:**

2.188 inches 1st end

**Connection Style:**

Raised swivel 2nd end

**Bolt Hole Diameter:**

0.266 inches and 0.276 inches 2nd end

**Raised Face Height:**

0.015 inches 2nd end

**Raised Face Diameter:**

1.854 inches 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

1200.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Hydrostatic Test Pressure:**

600.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Convuluted

**Measuring Method And Length:**

37.750 inches working and 38.250 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 1p322, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0