## NSN 4720-00-516-0879



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-516-0879 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** 250.0 degrees fahrenheit single response **Outside Diameter:** 0.875 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, chloroprene and 1st layer braided rayon cord **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and weatherproof **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 18.750 inches **Thread Series Designator:** Unf 1st end

## NSN 4720-00-516-0879

Nonmetallic Hose Assembly - Page 2 of 2



| _ |    |      |   |      |
|---|----|------|---|------|
| c | hο | JIF. |   | ife: |
| J |    |      | _ | HG.  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0