NSN 4720-00-516-0939

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-516-0939

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.281 inches
Minimum Inside Bending Radius:
9.500 inches
Connection Style:
Flared 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches
Media For Which Designed:

incula i oi willon besignea.

Fuel/oil, hydrocarbon single response

NSN 4720-00-516-0939

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	ator:
i i ii caa	OCI ICS	Design	ato.

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0