NSN 4720-00-520-2738

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-520-2738 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.672 inches **Minimum Inside Bending Radius:** 3.120 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Vacuum In Torr:** 50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

420.000 inches working

NSN 4720-00-520-2738

Nonmetallic Hose Assembly - Page 2 of 2



М	edia	For	Whic	h D	esian	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0