NSN 4720-00-521-6220

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-521-6220

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Connection Style: |
| Plain optional end 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal pipe 2nd end |
| Thready Qty Per Inch (tpi): |
| 18 2nd end |
| Burst Test Pressure: |
| 750.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber and 1st layer braided cotton cord |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 375.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Fuel resistant and mildew resistant and oil resistant and ozone resistant and cold resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 218.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |

NSN 4720-00-521-6220

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0