

View Online at <https://aerobasegroup.com/nsn/4720-00-522-1449>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.562 inches

Minimum Inside Bending Radius:

11.000 inches

End Application:

Hydraulic crane group, wrecker truck

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

1.000 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.750 inches and 18.250 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Specification Data:

Mil-h-13531 government specification

Specification Or Standard:

2 type and a class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.