NSN 4720-00-523-1462

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.260 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-523-1462

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.370 inches					
Minimum Inside Bending Radius:					
3.000 inches					
Exterior Color:					
Natural					
Connection Style:					
Swivel nut, flareless 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
12000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.562 inches 1st end					
Seat Angle:					
12.0 degrees 2nd end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Flow Angle:					
8.5 degrees 2nd end					
Outer Covering Environmental Protection:					
Corrosion resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
17.500 inches					

NSN 4720-00-523-1462

Nonmetallic Hose Assembly - Page 2 of 2



Th		Carias	Dania	
111	ıeau	Series	Desid	mator.

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0