## NSN 4720-00-523-2386

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-523-2386 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees celsius and 149.0 degrees celsius single response **Outside Diameter:** 0.484 inches **Minimum Inside Bending Radius:** 0.750 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided wire and 1st layer braided textile yarn and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 45.0 degrees 1st end **Outer Covering Environmental Protection:** Mildew resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

Unf 1st end

14.000 inches

**Thread Series Designator:** 

## NSN 4720-00-523-2386

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0