NSN 4720-00-523-3405

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches

Tempurature Rating:

450.0 degrees fahrenheit single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-523-3405

Outside Diameter:
Between 0.766 inches and 0.812 inches
Minimum Inside Bending Radius:
6.500 inches
Exterior Color:
Natural metallic
Connection Style:
Flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.0625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and corrosion resistant and fuel resistant
Vacuum In Torr:
254.0

NSN 4720-00-523-3405

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
32.250 inches working and 32.750 inches working
Special Features:
Burst pressure rated at 450.0 degrees f
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A542a0