Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-529-2833

Cross S	ectional Shape:
Round	
Thread I	Direction:
Right-ha	nd 1st end
Inside D	liameter:
0.411 inc	ches
Tempura	ature Rating:
-40.0 deg	grees fahrenheit and 250.0 degrees fahrenheit single response
Outside	Diameter:
0.770 inc	ches
Minimur	m Inside Bending Radius:
4.620 inc	ches
Exterior	Color:
Black	
Connect	tion Style:
Inverted	flare 1st end
End Cor	nnection Design:
Straight	1st end
Connect	tion Type:
Threade	d external pipe 1st end
Features	s Provided:
Reusable	e end fittings
Burst Te	est Pressure:
14000.0	pounds per square inch
Layer Co	omposition And Location:
2nd laye	r braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic
Maximu	m Operating Pressure:
3500.0 p	bounds per square inch
Thread \$	Size:
0.500 inc	ches 1st end
Seat An	gle:
30.0 deg	prees 1st end
Hydrost	atic Test Pressure:
7000.0 p	pounds per square inch
Inside S	Surface Condition:
Smooth	
Measuri	ng Method And Length:
28.500 ir	nches
Media F	or Which Designed:
Air and	fuel/oil, hydrocarbon single response
Thread \$	Series Designator:
Nptf 1st	end

## NSN 4720-00-529-2833

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

