Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-529-4997

| Cross Sectional Shape: | |
|--|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.375 inches | |
| Outside Diameter: | |
| 0.600 inches | |
| Minimum Inside Bending Radius: | |
| 3.000 inches | |
| Inner Conveying Tube Style: | |
| Helical open-pitch corrugated | |
| Connection Style: | |
| Swivel nut flare 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Identical ends | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 1850.0 pounds per square inch | |
| Thread Size: | |
| 0.562 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 2750.0 pounds per square inch | |
| Outer Covering Environmental Protection: | |
| Corrosion resistant and incombustible | |
| Measuring Method And Length: | |
| 11.750 inches | |
| Thread Series Designator: | |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 4720-00-529-4997

Metallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

