Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-529-4998

Cross	Sectional	Shape:
-------	-----------	--------

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.375 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

1.704 inches

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

2.250 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

800.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant and fire retardant

Inside Surface Condition:

Smooth



Measuring Method And Length:

24.750 inches working

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0